



## CARE & MAINTENANCE

Surfaces should be cleaned with a soft cloth and warm soapy water. Rinse and dry after cleaning. Under no circumstances should abrasive or acid based cleaning products be used.

## WARRANTY

This basin is warranted to be free from manufacturing defects for a period of:

Lifetime, stainless steel bowl

Pop-up waste, 1 year, parts and labour.

**This warranty does not cover against normal wear and will be voided if the product is misused or not installed in accordance with these instructions.**

 Scratching during use does not constitute a product or manufacturing fault.

In the event this product is rendered obsolete and a replacement product is required, Oliveri Solutions Pty Ltd reserves the right to supply a product of equal substitution at their discretion.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be acceptable quality and the failure does not amount to a major failure.

For full warranty information, visit: <https://oliveri.com.au/service-and-warranty>

## SINK SERVICE

If the basin requires servicing, please contact your installer (preferably the one who installed it). If the installer is satisfied that the problem is not due to poor installation, contact Oliveri's nominated **Warranty Service Agent**. For details visit:

<https://oliveri.com.au/service-and-warranty>

All warranty claims must be directed to our Warranty Service Agent. If the Warranty Service Agent finds that the basin is not faulty, they reserve the right to pass on any callout fee to the householder.

[oliveri.com.au](https://oliveri.com.au)




## MI50

## Rectangular Stainless Steel Inset Basin



THIS BASIN MUST BE INSTALLED BY A LICENSED PLUMBER IN ACCORDANCE WITH LOCAL REGULATIONS.

## INSTALLATION INSTRUCTIONS FOR INSET BASIN

Check the product for damage, if the product is damaged return to store of purchase.

Check the product is complete with all components required to install.

This product is to only be installed by a licensed plumber, failing to do so will void the warranty.

This product is to be installed as per Australian Standard and local authority requirements

### Inset Basin installation:

1. This basin is supplied with a cut-out template. Due to manufacturing variations it is recommended you cross check the cut-out template dimensions against the physical basin dimensions and adjust the cut-out size as, or if required.
2. Using the template dimensions, locate the basin cut-out in the desired position on the benchtop.
3. Prior to cutting the hole, check to ensure the cut-out will not interfere with drawers or internal walls of the vanity cabinet.

**NOTE: We recommend installing the basin so the Oliveri logo is positioned towards the back of the bench, and/or under the tap.**

4. Cut the hole into the vanity cabinet top.
5. Fit the basin into the cut-out hole to ensure the basin fits correctly and no further adjustment of the cut-out hole is required.

6. Prior to installing the basin, it is recommended the tapware and waste are fitted to the basin for ease of assembly.
7. Prior to fitting the basin to the bench top, run a plumbers grade silicone seal around the cut-out hole.
8. Insert the basin into the bench top cut-out and align so the basin is square to the vanity cabinet top.
9. Apply a bead of neutral cure silicone around the outer edge of the basin to prevent water going under the basin. Remove any excess silicone and allow the silicone to dry before proceeding with waste pipe installation.
10. Connect basin to drainage system as per Australian standards and local authority requirements.

**Benchtop cut out template:**

