



#### REMOVE EXCESS SEALANT AND MASKING

Excess sealant must be removed promptly with a suitable clean-up solvent recommended for use on both the counter/benchtap and stainless steel to ensure damage does not occur.



#### PLUMBING & TAPWARE

IMPORTANT - Connections to plumbing should always be done by a licensed plumber. Fit supplied basket wastes to sink bowls. Some models do not include basket wastes for every bowl. Install tapware according to manufacturers instructions.

If 2 or more individual basins/bowls are under-mounted, a minimum distance of 3 1/2" (90mm) is required between the basins/bowls. The counter/benchtap supplier is to determine the support method required.

It is essential that the installation is waterproof and carried out in accordance with these instructions. Tasman Sinkware will not be held responsible for any damage caused by leakage or faulty installation.

### CARE INSTRUCTIONS FOR YOUR OLIVERI STAINLESS STEEL SINK

**AVOID CONTACT WITH ROUGH OR DIRTY SURFACES as new polished stainless steel will show scratches!**



#### DO's

- Clean with soap & water (towel dry)
- Clean along the grain of the Stainless Steel
- Use a soft brush or sponge (old tooth brush)
- Wipe over with a glass cleaner (*Windex is very good*)
- Polish with a metal polish paste (*Autosol / Brasso*)
- Use a Liquid cleaner (*Bon-Ami or Jiff*)
- Use a granulated stainless steel cleaner (*Esstele*)



#### DO NOT's

- NEVER use Steel wool
- Beware of harsh liquid cleaners
- Beware of grit within cloths and mineral deposits within water
- Avoid prolonged exposure to acids from *Fruit, Fruit juices, Salts, Spirits, Bleach, Tea-bags*
- Avoid prolonged contact with ordinary steel which can rust *Tin Cans, Steelwool*
- Do not keep harsh (*acids or chlorine*) chemicals under sink / laundry tub
- Do not leave *chlorine/chloride chemicals* on stainless steel surface
- Do not leave *liquid soaps & cleaners to dry* on stainless steel
- Do not use bleaches (*White King, Domestos, Clorox*)

**AUSTRALIA**  
Head Office &  
Manufacturing Plant  
Tasman Sinkware Pty Ltd  
Regency Park SA

Phone: +61 8 8348 6444  
Fax: +61 8 8348 6495  
Email: sinkware@tasbuildpro.com.au

Tasman Sinkware  
is a division of  
Fletcher Building



© Tasman Sinkware 2006  
AU Under Mount Installation Instructions  
TF 45b.doc

#### NORTH AMERICA

**Sales Office**  
Tasman Sinkware North America  
Corona CA  
Email: northamerica@oliverisinks.com

#### UNITED KINGDOM DISTRIBUTOR

A.C. Toon Ltd  
Phone: 01246 223900  
Email: sales@actoon.co.uk

#### ASIA PACIFIC DISTRIBUTORS

**New Zealand - Dux Industries Ltd**  
Phone: 0800 367 389

**Singapore - Sim Siang Choon**  
Phone: 6266 6632

**Hong Kong - Deacon & Co Ltd**  
Phone: 2369 6111

## INSTALLER - PLEASE READ & FOLLOW THESE INSTALLATION INSTRUCTIONS

### FOR UNDERMOUNT SINKS

Please retain for consumer as care instructions are included



#### CHECK MODEL

The model number on the sink packaging must match the model of sink the customer ordered. **Do not install if incorrect.**




#### CHECK THE CONDITION

Inspect the sink for any visible defects. **Do not install the sink if defects are found.** Contact your sink retailer / point of purchase.



#### AVOID CUTS

The perimeter and punch-outs on the sink may contain sharp edges. Handle the sink carefully to avoid personal injury.



#### AVOID SCRATCHES

Polished stainless steel can be scratched if proper care is not taken during installation.

### EQUIPMENT REQUIRED for installing your Oliveri undermount sink:

#### MATERIALS FOR CUTTING BENCHTOP:

- **Template** for your particular model sink and mounting method (inside the carton)
- **Marker** such as a pencil or similar for tracing the template onto the counter/benchtap
- **Tape measure**
- **Drill with 12mm / 1/2" diameter bit** or larger (wood counter/benchtap)
- **Cutting Device** with suitable blade for counter/benchtap material
- **Suitable protection** such as gloves and goggles to be used while drilling or cutting



Download cutout  
template files  
(DWG & DXF)  
from our website.

#### MATERIALS FOR FITTING THE UNDERMOUNT SINK:

- **Oliveri sink** includes mounting clips, basket wastes and other accessories (depending on model).
- **These Installation Instructions**
- **Level** to check counter/benchtap & sink is installed level
- **Flat head screwdriver** (large - to tighten basket wastes)
- **Suitable sealant and fastening materials** (neutral-cure silicone sealant and structural epoxy or hardware)
- **Masking material** to protect counter/benchtap and sink from excess sealant
- **Clamping Mechanism** (such as threaded rod and timber bearers)
- **Additional Mounting Hardware** if fitting into thinner material. The instructions for bolting the sink require a minimum counter/benchtap thickness of 25mm / 1". Different hardware or packing materials will be needed for thin counters/benchtaps.

*Any advice, recommendation, information, assistance or service provided by Tasman Sinkware in relation to goods manufactured by it or their use and installation, is given in good faith and is believed by Tasman Sinkware to be appropriate and reliable. However, any advice, recommendation, information, assistance or service is provided by Tasman Sinkware without responsibility or liability.*



www.oliverisinks.com

